









Rotary Cam Switches

Technical Information Operators

Operator variants for mounting forms with escutcheon and handle

| Operator Suitable for Types | | Colour escutcheon | Colour legend plate | Colour operator | Change of order code number |
|--|---|----------------------|------------------------|--------------------|--------------------------------|
| M-handle P110, P220, P225, M220, M225, T225, S432, S440, S606, S608, S612 |  | black | silver | black | - - ...M1 |
| | | grey | silver | grey | - - ...M2 |
| | | white | silver | white | - - ...M3 |
| | | black | yellow | red | - - ...M4 |
| | | black | silver | red | - - ...M5 |
| | | black | black | black | - - ...M8 |
| F-handle P220, P225, M220, M225, T225 |  | black | silver | black | - - ...F1 |
| | | grey | silver | grey | - - ...F2 |
| | | white | silver | white | - - ...F3 |
| | | black | yellow | red | - - ...F4 |
| | | black | silver | red | - - ...F5 |
| | | black | black | black | - - ...F8 |
| B-handle P220, P225, M220, M225, T225, S432, S440, S606, S608, S612, S825 |  | black | silver | black | - - ...B1 |
| | | grey | silver | grey | - - ...B2 |
| | | white | silver | white | - - ...B3 |
| | | black | yellow | red | - - ...B4 |
| | | black | silver | red | - - ...B5 |
| | | black | black | black | - - ...B8 |
| N-handle P220, P225, M220, M225, T225, S432, S440 |  | black | silver | black | - - ...N1 |
| | | grey | silver | grey | - - ...N2 |
| | | white | silver | white | - - ...N3 |
| | | black | yellow | red | - - ...N4 |
| | | black | silver | red | - - ...N5 |
| | | black | black | black | - - ...N8 |
| G-handle S432, S440, S606, S608, S612, S825 |  | black | silver | black | - - ...G1 |
| | | black | yellow | red | - - ...G4 |
| | | black | silver | red | - - ...G5 |
| | | black | black | black | - - ...G8 |
| R-handle P220, P225, M220, M225, T225, S432, S440 |  | black | silver | black | - - ...R1 |
| | | grey | silver | grey | - - ...R2 |
| | | white | silver | white | - - ...R3 |
| | | black | yellow | red | - - ...R4 |
| | | black | silver | red | - - ...R5 |
| | | | | | |
| Installation mounting for 45 mm aperture in Panel/Distribution boards: | | | | | |
| M-handle P220, P225, M220, M225, T225 |  | grey | silver | black | - - ...M1 |
| | | grey | silver | grey | - - ...M2 |
| | | grey | yellow | red | - - ...M4 |
| | | | | | |
| N-handle P220, P225, M220, M225, T225 |  | grey | silver | black | - - ...N1 |
| | | grey | silver | grey | - - ...N2 |
| | | grey | yellow | red | - - ...N4 |
| | | | | | |

Operator variants for mounting forms with padlock device

| Operator Suitable for Types | | Colour escutcheon | Colour legend plate | Colour operator | Change of order code number |
|--|--|--|---|--|--------------------------------|
| N-padlock device P220, P225, M220, M225, T225, S432, S440, S606, S608, S612 | | black | white | black | ... - ... - ... N1 |
| | | grey | white | grey | ... - ... - ... N2 |
| | | yellow | white | red | ... - ... - ... N4 |
| | | grey | white | black | ... - ... - ... N6 |
| | | yellow | white | black | ... - ... - ... N7 |
| | | operator external dimension 67 × 67 mm 88 × 88 mm | max. number of padlocks 3 4 | hasp diameter of padlock 4 mm (min) / 8 mm (max) 5 mm (min) / 9 mm (max) | |
| M-padlock device P110, P220, P225, M220, M225, T225, S432, S440, S606, S608, S612 | | black | white | black | ... - ... - ... M1 |
| | | grey | white | grey | ... - ... - ... M2 |
| | | yellow | white | red | ... - ... - ... M4 |
| | | grey | white | black | ... - ... - ... M6 |
| | | yellow | white | black | ... - ... - ... M7 |
| | | operator external dimension 48 × 48 mm 67 × 67 mm 88 × 88 mm | max. number of padlocks 3 3 4 | hasp diameter of padlock 3 mm (min) / 5 mm (max) 4 mm (min) / 8 mm (max) 5 mm (min) / 9 mm (max) | |
| B-padlock device S432, S440, S606, S608, S612, S825 | | black | silver | black | ... - ... - ... B1 |
| | | black | yellow | red | ... - ... - ... B4 |
| | | black | black | black | ... - ... - ... B8 |
| | | operator external dimension 75 × 114 mm 98 × 142 mm 130 × 178 mm | max. number of padlocks 4 4 4 | hasp diameter of padlock 5 mm (min) / 8 mm (max) 5 mm (min) / 8 mm (max) 5 mm (min) / 8 mm (max) | |
| H-padlock device S432, S440, S606, S608, S612, S825 | | black | silver | black | ... - ... - ... H1 |
| | | black | yellow | red | ... - ... - ... H4 |
| | | black | black | black | ... - ... - ... H8 |
| | | operator external dimension 75 × 114 mm 98 × 142 mm 130 × 178 mm | max. number of padlocks 4 4 4 | hasp diameter of padlock 5 mm (min) / 8 mm (max) 5 mm (min) / 8 mm (max) 5 mm (min) / 8 mm (max) | |
| Padlockable with V-handle P110, P220, P225, M220, M225, T225, S432, S440 | | black | silver | black | ... - ... - ... V1 |
| | | black | yellow | red | ... - ... - ... V4 |
| | | operator external dimension 48 × 48 mm 64 × 64 mm | max. number of padlocks 2 3 | hasp diameter of padlock 3 mm (min) / 5 mm (max) 4 mm (min) / 6 mm (max) | |
| Padlockable with L-handle P110, P220, P225, M220, M225, T225 | | black | silver | black | ... - ... - ... L1 |
| | | black | yellow | red | ... - ... - ... L4 |
| | | operator external dimension 48 × 48 mm | max. number of padlocks 2 | hasp diameter of padlock 3 mm (min) / 5 mm (max) | |
| Installation mounting for 45 mm aperture in Panel/Distribution boards: | | | | | |
| Padlockable with V-handle P220, P225, M220, M225 T225 | | grey | silver | black | ... - ... - ... V1 |
| | | grey | yellow | red | ... - ... - ... V4 |
| | | operator external dimension 45 × 52.5 mm | max. number of padlocks 2 | hasp diameter of padlock 3 mm (min) / 5 mm (max) | |
| Padlockable with L-handle P220, P225, M220, M225, T225 | | grey | silver | black | ... - ... - ... L1 |
| | | grey | yellow | red | ... - ... - ... L4 |
| | | operator external dimension 45 × 52.5 mm | max. number of padlocks 2 | hasp diameter of padlock 3 mm (min) / 5 mm (max) | |